

## Wendy's Meat Well

48.00" Deep Self-Contained Refrigerated Meat Well Unit

## Custom Sku

48.00" Deep Self-Contained Refrigerated Meat Well Unit .



located behind storage area. Base is equipped with independently controlled thermostat, solenoid valve and condensate evaporator. On/off switch for unit is located behind louver in compressor housing. Rail on/off switch is located on the exterior side panel. Refrigeration system in the base will maintain 36°F (2°C) to 40°F (4°C).

Standard Features · Stainless steel back with louvers at the

· High density environmentally friendly, Kyoto

· Snap-in dart style vinyl magnetic gasket

 Environmentally friendly HFC-R290 refrigerant · One year parts and labor standard warranty

compressor housing

Protocol Compliant, Non ODP • (Ozone Depletion Potential), Non GWP (Global Warming Potential) polyurethane foam

insulation throughout unit

· Five year compressor warranty

 S/S Legs w/ flanged feet • (3) 12" adapter bars for cold well

One shelf

8' cord and plug

Flanged Feet: The unit is mounted on 6" flanged feet.

Electrical connections are 115 volt, 60 Hertz, single phase. Unit is wired with 8' (2.4m) cord and plug.

Project	
Item	2
Quantity	ח
CSI Section 11400	
Approved	J
Date	U



## **Specifications**

Exterior top is one-piece, stainless steel, with integral 2.12" (5 cm) high square nosing on front. Top has a mechanically cooled refrigerated well with openings to accommodate (1) full and (1) 1/3 size pans 6" deep, provided by others. (3) 12" adapter bars are provided. Pans are recessed 2" (5 cm). Well interior is stainless steel, and has one hinged removable covers. Unit is equipped with separate expansion valve and on/off switch for refrigerated cold pan. Temperature in top opening to maintain 33°F (1°C) to 41°F (5°C) with pans recessed 2" (5 cm) at 86°F ambient room temperature, meeting NSF7 requirements

Exterior back and ends are stainless steel. Bottom is galvanized steel.

Base Interior is stainless steel. Base door frames are thermoformed ABS plastic. Base is insulated with 1.5' (4 cm) high density foamed in place environmentally friendly, Kyoto Protocol Compliant, Non ODP (Ozone Depletion Potential), Non GWP (Global Warming Potential) polyurethane. Back of base has a machine compartment, with condensing unit installed.

Door has a stainless steel exterior front, with thermoformed ABS plastic interior liner, black recessed handle and snap in magnetic gasket which is easily replaceable. Door section has (1) removable epoxy coated wire shelf.

Refrigeration System uses HFC-R920 refrigerant. Cabinet has a blower coil assembly with expansion valve

980 S. Isabella Rd. Mt. Pleasant, Michigan 48858

Phone: 800-733-8948 or 989-773-7981 Fax: 800-669-0619 www.delfield.com

Printed in the U.S.A. 7879B 03/22





ISF

R290





Welbilt reserves the right to make changes to the design or specifications without prior notice.

980 S. Isabella Rd. Mt. Pleasant, Michigan 48858 Phone: 800-733-8948 or 989-773-7981 Fax: 800-669-0619 www.delfield.com Printed in the U.S.A. 7879B 03/22

